



FTXP-L / RXP-L

Wall mounted unit for low energy consumption and all round comfort

- > Seasonal efficiency values up to A++ in cooling and heating
- > Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview of your energy consumption
- > Quiet in operation down to 20 dBA
- > Choosing an R-32 product, reduces the environmental impact by 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- > **Econo mode:** Decreases power consumption so that other appliances that need large power consumption can be used. This function is also energy saving
- > **Indoor unit silent operation:** "Silent" button on the remote control lowers the operation sound of the indoor unit by 3dB(A)
- > **Air filter:** Removes airborne dust particles to ensure a steady supply of clean air

R-32 BLUEEVOLUTION



FTXP20-35L



RXP20-35L



BRC073 (optional)



ARC480A11



BRP069B42 (optional)



WI-FI ADAPTOR
AVAILABLE AS AN OPTION

FTXP-L / RXP-L

R-32 BLUEEVOLUTION

Indoor Units			FTXP20L	FTXP25L	FTXP35L	FTXP50L	FTXP60L	FTXP71L
Capacity	UK Total Cooling	kW	1.95	2.44	3.42	4.89	5.86	6.93
	UK Sensible Cooling	kW	1.65	1.82	2.56	3.42	4.00	4.73
	Nominal Cooling	kW	2.0	2.5	3.5	5.0	6.0	7.1
	Nominal Heating	kW	2.5	3.0	4.0	6.0	7.0	8.2
Seasonal Efficiency (EN14825) COOLING	Energy Label		A++	A++	A++	A++	A++	A
	Pdesign	kW	2.0	2.5	3.5	5.0	6.0	7.1
	SEER		6.79	6.92	6.62	6.72	6.82	5.30
	Annual Energy Consumption kWh		104	127	186	260	308	469
Seasonal Efficiency (EN14825) HEATING	Energy Label		A++	A++	A++	A+	A+	A
	Pdesign	kW	2.2	2.4	2.8	4.6	4.8	6.2
	SCOP		4.65	4.61	4.64	4.10	4.10	3.81
	Annual Energy Consumption kWh		662	728	845	1571	1640	2279
Nominal Efficiency	EER/COP		4.02/4.77	3.83/4.36	3.49/4.02	3.61/3.80	3.29/3.63	2.64/3.19
Air Flow Rate (Cooling)	High / Nom / Low / Silent	m ³ /sec	0.163 / 0.131 / 0.098 / 0.073	0.168/0.135/ 0.101/0.073	0.191/0.138/ 0.105/0.075	0.280/0.240/ 0.198/0.175	0.288/0.246/ 0.203/0.178	0.295/0.253/ 0.210/0.185
Dimensions	Height	mm	286	286	286	295	295	295
	Width	mm	770	770	770	990	990	990
	Depth	mm	225	225	225	263	263	263
Weight		kg	9	9	9	14	14	14
Sound Pressure (Cooling)	High / Nom/ Low / Silent	dBA	39/33/25/20	40/33/26/20	43/34/27/20	43/39/34/31	45/41/36/33	46/42/37/34
Sound Pressure (Heating)	High / Nom / Low / Silent	dBA	39/34/28/21	40/34/28/21	40/35/29/21	42/38/33/30	44/40/35/32	45/41/36/33
Sound Power (Cooling)		dBA	55	55	58	59	60	62

Outdoor Units			RXP20L	RXP25L	RXP35L	RXP50L	RXP60L	RXP71L
Dimensions	Height x Width x Depth	mm	550 X 658 X 275	550 X 658 X 275	550 X 658 X 275	735 x 825 x 300	735 x 825 x 300	734 x 870 x 320
Weight		kg	28	28	28	47	47	56
Electrical Details	Power Supply		1ph	1ph	1ph	1ph	1ph	1ph
	Running Current	A	2.47	3.25	5.42	6.42	8.24	11.94
	Max Fuse Size	A	16	16	16	15	15	20
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 5/8 (15.9)
Pipework	Maximum Length	m	15	15	15	30	30	30
	Maximum Vertical Rise	m	12	12	12	20	20	20
	Precharged to	m	10	10	10	10	10	10
	Additional charge	g/m	20	20	20	20	20	20
	Holding charge	kg	0.7	0.7	0.7	1.40	1.45	1.45
Sound Pressure (Cooling)	Nominal	dBA	46	46	48	47	49	52
Sound Pressure (Heating)	Nominal	dBA	47	47	48	49	49	52
Sound Power (Cooling)		dBA	60	60	62	61	63	66
Operating Range (Cooling)	Min / Max	°CDB	-10 / 46	-10 / 46	-10 / 46	-10 / 46	-10 / 46	-10 / 46
Operating Range (Heating)	Min / Max	°CWB	-15 / 18	-15 / 18	-15 / 18	-15 / 18	-15 / 18	-15 / 18
Air Flow Rate (Cooling)	Nominal	m ³ /sec	0.600	0.600	0.600	0.840	0.840	1.122
ECA Eligible			●	●	●	●	●	

Accessory Ref	Description
BRC073	Optional Wired Remote controller: BRC1E53 style
BRP069B42	Wifi adaptor for connection to on-line controller
BRCW901A03	3m connection cable for BRC073
BRCW901A08	8m connection cable for BRC073
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with Split ODU - tray width 800mm
K.CG5	Condensing Unit Guard size 20-35
K.CGM	Condensing Unit Guard size 42-71
KRP413A1S	Adaptor PCB for remote on/off control - constant/pulse contact

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU), Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com